

Radius 45^{HD}

Owners Manual

Specifications

Frequency Response	Sensitivity (1W@1M)	Nominal Impedance	Power Handling Single (RMS)	System Power Handling (RMS)	Recommended Amp Requirements
120Hz - 20KHz	87dB	8 Ohms	25W	50W	5-50 W

Maximum SPL (dBA)	Bass Alignment	Drive Unit Complement	External Dimensions. mm (H x W x D)	External Dimensions. inch (H x W x D)	Weight (each) Kg (lb)
101	Sealed Cabinet	1x 3" MMP2 cone mid-bass driver. 1 x 20mm C-CAM gold dome tweeter	100 x 100 x 100	3 15/16 x 3 15/16 x 3 15/16	0.95 (2 1/8)

Guarantee and Service

To validate your warranty please visit www.monitoraudio.co.uk within 30 days of purchase.

When you register here you'll gain free entry to our monthly prize draw! What's more you'll be the first to hear about the great things happening at Monitor Audio, including new products and events!

This equipment has been fully tested prior to dispatch from the factory. Both the craftsmanship and the performance of this product is guaranteed against manufacturing defects for the period of **three years** from the date of purchase (see conditions below), provided that the product was supplied by an authorised Monitor Audio retailer under the consumer sale agreement. (The words 'consumer sale' shall be construed in accordance with section 15 of the supply of goods act 1973). Monitor Audio accepts no responsibility for defects arising from accident, misuse, abuse, wear and tear, modification or operation outside of that specified within this instruction manual. Neither will responsibility be accepted for damage or loss occurring during transit to or from the parties claiming under this guarantee.

This guarantee covers both labour and parts. The liability of Monitor Audio is limited to the cost of repair or replacement of the defective parts (at the discretion of Monitor Audio) and under no circumstances extends to consequential losses or damage.